

057116-02

DOE/OR/20722-168

m-038

Formerly Utilized Sites Remedial Action Program (FUSRAP)
Contract No. DE-AC05-81OR20722

**RADIOLOGICAL CHARACTERIZATION
REPORT FOR THE RESIDENTIAL
PROPERTY AT 11 BRANCA COURT**

Lodi, New Jersey

November 1988



Bechtel National, Inc.

057116

Bechtel National, Inc.

Systems Engineers — Constructors

Jackson Plaza Tower
800 Oak Ridge Turnpike
Oak Ridge, Tennessee 37830



Mail Address: P.O. Box 3001, Oak Ridge, TN 37831-0301
Telex: 3785873

NOV 1 1988

U.S. Department of Energy
Oak Ridge Operations
Post Office Box 2001
Oak Ridge, Tennessee 37831-8723

Attention: Peter J. Gross, Director
Technical Services Division

Subject: Bechtel Job No. 14501, FUSRAP Project
DOE Contract No. DE-AC05-81OR20722
Publication of the Radiological Characterization Reports
for the Residential Properties at 7 Branca Court,
11 Branca Court, 16 Long Valley Road, 18 Long Valley
Road, 20 Long Valley Road, 22 Long Valley Road, 26 Long
Valley Road, 11 Redstone Lane, and the Lodi Municipal
Park, in Lodi, New Jersey
Code: 7310/WBS: 138

Reference: Letter from S. K. Oldham (DOE), 88-669 dated October 19,
1988, to B. W. Clemens (BNI), "Final Comments on the
Prepublication Draft of the Radiological
Characterization Reports for the Residential Properties
at 7 Branca Court, 11 Branca Court, 16 Long Valley Road,
18 Long Valley Road, 20 Long Valley Road, 22 Long Valley
Road, 26 Long Valley Road, 11 Redstone Lane, and the
Lodi Municipal Park, in Lodi, New Jersey," CCN 056527.

Dear Mr. Gross:

Enclosed are six copies each of the published version of the nine
characterization reports listed above. Incorporated in these
reports are comments based on the reference above and additional
discussions between N. C. Ring and S. K. Oldham of your office and
J. D. Berger of ORAU.

Peter J. Gross

2

These publications also incorporate changes in wording regarding site release as requested by S. K. Oldham and A. Avel.

Please notify me should you require additional copies (6-1677).

Very truly yours,

B. W. Clemens

B. W. Clemens *for*
Project Manager - FUSRAP

CONCURRENCE

BWC/skl:1750x

Enclosures: As stated

SKL	EG			
-----	----	--	--	--

cc: R. G. Atkin, w/o
J. D. Berger, ORAU (w/all enclosures)
G. K. Hovey, w/o
B. A. Hughlett, w/o
M. R. McDougall, TMA/E (w/all enclosures)
S. K. Oldham, w/o
R. Rosen, EPA Region II, w/o
R. E. Swaja, ORNL, w/o
J. F. Wing, w/o

RADIOLOGICAL CHARACTERIZATION REPORT
FOR THE RESIDENTIAL PROPERTY
AT 11 BRANCA COURT
LODI, NEW JERSEY

NOVEMBER 1988

Prepared for

UNITED STATES DEPARTMENT OF ENERGY
OAK RIDGE OPERATIONS OFFICE
Under Contract No. DE-AC05-81OR20722

By

N. C. Ring and S. K. Livesay
Bechtel National, Inc.
Oak Ridge, Tennessee

Bechtel Job No. 14501

TABLE OF CONTENTS

	<u>Page</u>
Abbreviations	v
1.0 Introduction and Summary	1
1.1 Introduction	1
1.2 Purpose	1
1.3 Summary	3
2.0 Site History	6
2.1 Previous Radiological Surveys	7
2.2 Remedial Action Guidelines	7
3.0 Health and Safety Plan	11
3.1 Subcontractor Training	11
3.2 Safety Requirements	11
4.0 Characterization Procedures	13
4.1 Field Radiological Characterization	13
4.1.1 Measurements Taken and Methods Used	13
4.1.2 Sample Collection and Analysis	14
4.2 Building Radiological Characterization	17
5.0 Characterization Results	19
5.1 Field Radiological Characterization	19
5.2 Building Radiological Characterization	20
References	32
Appendix A - Geologic Drill Logs for 11 Branca Court	A-1

LIST OF FIGURES

<u>Figure</u>	<u>Title</u>	<u>Page</u>
1-1	Location of Lodi Vicinity Properties	2
1-2	Location of 11 Branca Court	4
4-1	Borehole Locations at 11 Branca Court	15
4-2	Surface and Subsurface Soil Sampling Locations at 11 Branca Court	16
5-1	Areas of Surface Contamination at 11 Branca Court	21
5-2	Areas of Subsurface Contamination at 11 Branca Court	22

LIST OF TABLES

<u>Table</u>	<u>Title</u>	<u>Page</u>
2-1	Summary of Residual Contamination Guidelines for the Lodi Vicinity Properties	9
5-1	Surface and Subsurface Radionuclide Concentrations in Soil for 11 Branca Court	24
5-2	Downhole Gamma Logging Results for 11 Branca Court	26

ABBREVIATIONS

cm	centimeter
cm ²	square centimeter
cpm	counts per minute
dpm	disintegrations per minute
ft	foot
h	hour
in.	inch
l	liter
l/min	liters per minute
m	meter
m ²	square meter
MeV	million electron volts
μR/h	microroentgens per hour
mi	mile
mi ²	square mile
min	minute
mrad/h	millirad per hour
mrem	millirem
mrem/yr	millirem per year
pCi/g	picocuries per gram
pCi/l	picocuries per liter
WL	working level
yd	yard
yd ³	cubic yards

1.0 INTRODUCTION AND SUMMARY

1.1 INTRODUCTION

The 1984 Energy and Water Appropriations Act authorized the U.S. Department of Energy (DOE) to conduct a decontamination research and development project at four sites, including the site of the former Maywood Chemical Works (now owned by the Stepan Company) and its vicinity properties. The work is being administered by the Formerly Utilized Sites Remedial Action Program (FUSRAP), one of two remedial action programs under the direction of the DOE Division of Facility and Site Decommissioning Projects. The residential properties in Lodi, New Jersey, are included in FUSRAP as vicinity properties. Figure 1-1 shows the location of the Lodi vicinity properties in relation to the former Maywood Chemical Works.

The United States Government initiated FUSRAP in 1974 to identify, clean up, or otherwise control sites where low activity radioactive contamination (exceeding current guidelines) remains from the early years of the nation's atomic energy program or from commercial operations that resulted in conditions Congress has mandated DOE to remedy (Ref. 1).

FUSRAP is currently being managed by DOE Oak Ridge Operations. As the Project Management Contractor for FUSRAP, Bechtel National, Inc. (BNI) is responsible to DOE for planning, managing, and implementing FUSRAP.

1.2 PURPOSE

The purpose of the 1986 survey performed by BNI was to locate the horizontal and vertical boundaries of radionuclide concentrations exceeding remedial action guidelines.




FIGURE 1-1 LOCATION OF LODI VICINITY PROPERTIES

1.3 SUMMARY

This report summarizes the procedures and results of the radiological characterization of the property at 11 Branca Court (Figure 1-2) in Lodi, New Jersey, conducted from September through December 1986.

Ultimately, the data generated during the radiological characterization will be used to define the complete scope of remedial action necessary to release the site.

This characterization confirmed that thorium-232 is the primary radioactive contaminant at this property. Results of surface soil samples for 11 Branca Court showed maximum concentrations of thorium-232 and radium-226 to be 11.3 and 2.0 pCi/g, respectively. Subsurface soil sample concentrations ranged from 1.0 to 9.4 pCi/g for thorium-232 and from 0.5 to 2.0 pCi/g for radium-226. The average background level in this area for both radium-226 and thorium-232 is 1.0 pCi/g.

Historical information indicates that uranium is not a primary contaminant in this area; therefore, analysis for uranium was not considered critical for this characterization. The soil samples have been archived and, if necessary, can be analyzed for uranium at some future date. Because the major contaminants at the vicinity properties are thorium and radium, the decontamination guidelines provide the appropriate guidance for the cleanup activities. DOE believes that these guidelines are conservatively low for considering potential adverse health effects that might occur in the future from any residual contamination. The dose contributions from uranium and any other radionuclides not numerically specified in these guidelines are not expected to be significant following decontamination. In addition, because the vicinity properties will be decontaminated in a manner to reduce future doses to levels that are as low as reasonably achievable (ALARA), DOE will ensure that most of the radioactivity present at these vicinity properties will be removed during the cleanup (Ref. 2).




FIGURE 1-2 LOCATION OF 11 BRANCA COURT

Soil analysis data for this property showed surface contamination. Subsurface investigation by gamma logging indicated contamination to a depth of 8.5 ft.

The radon-222 measurements inside the residence indicated a concentration less than 0.8 pCi/l, which is within the DOE guideline of 3.0 pCi/l.

Measurements for radon daughters ranged from 0.003 to 0.004 WL. Measurements were made for thoron daughters; however, results were negligible.

2.0 SITE HISTORY

The Maywood Chemical Works was founded in 1895. During World War I (in 1916), the company began processing thorium from monazite sand for use in manufacturing gas mantles for various lighting devices. The company continued this work until 1956. Process wastes from manufacturing operations were pumped to two areas surrounded by earthen dikes (northern and southern diked areas) on property west of the plant. Subsequently, some of the contaminated wastes migrated onto adjacent and vicinity properties.

In 1928 and again between 1944 and 1946, some of the residues from the processing operations were moved from the company's property and used as mulch and fill in nearby low-lying areas. The fill material consisted of tea and cocoa leaves mixed with other material resulting from operations at the plant and apparently also contained thorium process wastes (Ref. 3).

It is not known for certain how the properties in Lodi were contaminated. According to an area resident, fill from an unknown source was brought to Lodi and spread over large portions of the previously low-lying and swampy area. For several reasons, however, a more plausible explanation is that the contamination migrated along a drainage ditch originating on the Maywood Chemical Works property. It can be seen from photographs and tax maps of the area that the course of a previously existing stream known as Lodi Brook, which originated at the former Maywood Chemical Works, generally coincides with the path of contamination in Lodi. The brook was subsequently replaced by a storm drain system as the area was developed. Secondly, samples taken from Lodi properties indicate elevated concentrations of a series of elements known as rare earths. Rare earth elements are typically found in monazite sands, which also include thorium. This type of sand was feedstock at the Maywood Chemical Works, and elevated levels are known to exist in the by-product of the extraction process. Third, the ratio of thorium to other radionuclides found in these Lodi properties is

comparable to the ratio found in contaminated material on other properties in Lodi (Ref. 4). And finally, long-time residents of Lodi recall chemical odors in and around the brook in Lodi and steam rising off the water. These observations suggest discharges of contaminants occurring upstream.

The Stepan Chemical Company (now called the Stepan Company) purchased Maywood Chemical Works in 1959. The Stepan Company itself has never been involved in the manufacture or processing of any radioactive materials (Ref. 5).

2.1 PREVIOUS RADIOLOGICAL SURVEYS

January 1981 - The Nuclear Regulatory Commission (NRC) directed that a survey of the Stepan Company property and its vicinity be conducted. Using the Stepan Company plant as the center, a 4-mi² aerial survey conducted by the EG&G Energy Measurements Group identified anomalous concentrations of thorium-232 to the north and south of the Stepan Company property. The Lodi residential properties were included in this survey (Ref. 6).

June 1984 - In June 1984, Oak Ridge National Laboratory (ORNL) conducted a "drive by" survey of Lodi using its "scanning van." Although not comprehensive, the survey indicated areas requiring further investigation (Ref. 7).

September 1986 - At the request of DOE, ORNL conducted radiological surveys of the vicinity properties in Lodi, New Jersey, for the purpose of determining which properties contained radioactive contamination in excess of guidelines and would require remedial action (Ref. 8).

2.2 REMEDIAL ACTION GUIDELINES

Table 2-1 summarizes the DOE guidelines for residual contamination. The thorium-232 and radium-226 limits listed in Table 2-1 will be

used to determine the extent of remedial action required at the vicinity properties. DOE developed these guidelines to be consistent with the guidelines established by the Environmental Protection Agency (EPA) for the Uranium Mill Tailings Remedial Action Program.

TABLE 2-1

SUMMARY OF RESIDUAL CONTAMINATION GUIDELINES FOR THE LODI VICINITY PROPERTIES

Page 1 of 2

BASIC DOSE LIMITS

The basic limit for the annual radiation dose received by an individual member of the general public is 100 mrem/yr.

SOIL (LAND) GUIDELINES (MAXIMUM ALLOWABLE LIMITS)

Radionuclide

Soil Concentration (pCi/g) above background^{a,b,c}

Radium-226

5 pCi/g, averaged over the first 15 cm of soil below

Radium-228

the surface; 15 pCi/g when averaged over any 15-cm-

Thorium-230

thick soil layer below the surface layer.

Thorium-232

STRUCTURE GUIDELINES (MAXIMUM ALLOWABLE LIMITS)

Airborne Radon Decay Products

Generic guidelines for concentrations of airborne radon decay products shall apply to existing occupied or habitable structures on private property; structures that will be demolished or buried are excluded. The applicable generic guideline (40 CFR 192) is: In any occupied or habitable building, the objective of remedial action shall be, and reasonable effort shall be made to achieve, an annual average (or equivalent) radon decay product concentration (including background) not to exceed 0.02 WL.^d In any case, the radon decay product concentration (including background) shall not exceed 0.03 WL. Remedial actions are not required in order to comply with this guideline when there is reasonable assurance that residual radioactive materials are not the cause.

External Gamma Radiation

The average level of gamma radiation inside a building or habitable structure on a site shall not exceed the background level by more than 20 µR/h.

Indoor/Outdoor Structure Surface Contamination

Allowable Residual Surface Contamination^e
(dpm/100 cm²)

Radionuclide^f

Average^{g,h}

Maximum^{h,i}

Removable^{h,j}

Transuranics, Ra-226, Ra-228, Th-230, Th-228
Pa-231, Ac-227, I-125, I-129

100

300

20

Th-Natural, Th-232, Sr-90, Ra-223, Ra-224
U-232, I-126, I-131, I-133

1,000

3,000

200

TABLE 2-1
(continued)

Page 2 of 2

Indoor/Outdoor Structure Surface Contamination (continued)

<u>Radionuclide</u> ^f	<u>Allowable Residual Surface Contamination^e</u> <u>(dpm/100 cm²)</u>		
	<u>Average</u> ^{g,h}	<u>Maximum</u> ^{h,i}	<u>Removable</u> ^{h,j}
U-Natural, U-235, U-238, and associated decay products	5,000 α	15,000 α	1,000 α
Beta-gamma emitters (radionuclides with decay modes other than alpha emission or spontaneous fission) except Sr-90 and others noted above	5,000 β-γ	15,000 β-γ	1,000 β-γ

^aThese guidelines take into account ingrowth of radium-226 from thorium-230 and of radium-228 from thorium-232, and assume secular equilibrium. If either thorium-230 and radium-226 or thorium-232 and radium-228 are both present, not in secular equilibrium, the guidelines apply to the higher concentration. If other mixtures of radionuclides occur, the concentrations of individual radionuclides shall be reduced so that the dose for the mixtures will not exceed the basic dose limit.

^bThese guidelines represent residual concentrations above background averaged across any 15-cm-thick layer to any depth and over any contiguous 100-m² surface area.

^cLocalized concentrations in excess of these limits are allowable provided that the average concentration over a 100-m² area does not exceed these limits.

^dA working level (WL) is any combination of short-lived radon decay products in 1 liter of air that will result in the ultimate emission of 1.3×10^5 MeV of potential alpha energy.

^eAs used in this table, dpm (disintegrations per minute) means the rate of emission by radioactive material as determined by correcting the counts per minute observed by an appropriate detector for background, efficiency, and geometric factors associated with the instrumentation.

^fWhere surface contamination by both alpha- and beta-gamma-emitting radionuclides exists, the limits established for alpha- and beta-gamma-emitting radionuclides should apply independently.

^gMeasurements of average contamination should not be averaged over more than 1 m². For objects of less surface area, the average shall be derived for each such object.

^hThe average and maximum radiation levels associated with surface contamination resulting from beta-gamma emitters should not exceed 0.2 mrad/h and 1.0 mrad/h, respectively, at 1 cm.

ⁱThe maximum contamination level applies to an area of not more than 100 cm².

^jThe amount of removable radioactive material per 100 cm² of surface area should be determined by wiping that area with dry filter or soft absorbent paper, applying moderate pressure, and measuring the amount of radioactive material on the wipe with an appropriate instrument of known efficiency. When removable contamination on objects of surface area less than 100 cm² is determined, the activity per unit area should be based on the actual area and the entire surface should be wiped. The numbers in this column are maximum amounts.

3.0 HEALTH AND SAFETY PLAN

BNI is responsible for protecting the health of personnel assigned to work at the site. As such, all subcontractors and their personnel are required to comply with the provisions of the applicable project instructions cited in this section or as directed by the on-site BNI representative.

3.1 SUBCONTRACTOR TRAINING

Before the start of work, all subcontractor personnel attend an orientation session presented by the BNI representative to explain the nature of the material to be encountered in the work and the required personnel monitoring and safety measures.

3.2 SAFETY REQUIREMENTS

Subcontractor personnel must comply with the following BNI requirements.

- o Bioassay - Subcontractor personnel submit bioassay samples before or at the beginning of on-site activity, upon completion of the activity, and periodically during site activities as requested by BNI.
- o Protective Clothing/Equipment - Subcontractor personnel are required to wear the protective clothing/equipment specified in the subcontract or as directed by the BNI representative.
- o Dosimetry - Subcontractor personnel are required to wear, and return daily, the dosimeters and monitors issued by BNI.
- o Controlled Area Access/Egress - Subcontractor personnel and equipment entering areas wherein access and egress are controlled for radiation and/or chemical safety purposes are surveyed by the BNI representative for contamination before leaving those areas.
- o Medical Surveillance - Upon written direction from BNI, subcontractor personnel who work in areas where hazardous chemicals might exist are given a baseline and periodic health assessment defined in BNI's Medical Surveillance Program.

Radiation and/or chemical safety surveillance of all activities related to the scope of work is under the direct supervision of personnel representing BNI.

The health physics requirements for all activities involving radiation or radioactive material are defined in Project Instruction No. 20.01, the Project Radiation Protection Manual and implementing procedures.

The industrial hygiene requirements for activities involving chemicals or chemically contaminated materials are defined in Project Instruction No. 26.00, the Environmental Hygiene Manual and implementing procedures.

Copies of these project instructions and manuals are located on-site for the use of subcontractor personnel.

4.0 CHARACTERIZATION PROCEDURES

A master grid was established by the surveyor; BNI's radiological support subcontractor, Thermo Analytical/Eberline (TMA/E), established a grid on individual properties. The size of the grid blocks is adjusted to adequately characterize each property. The grid origin allows the grid to be reestablished during remedial action and is correlated with the New Jersey state grid system. All data correspond to coordinates on the characterization grid. The grid and its east and north coordinates are shown on all figures of the property (Sections 4 and 5).

4.1 FIELD RADIOLOGICAL CHARACTERIZATION

4.1.1 Measurements Taken and Methods Used

An initial walkover survey using unshielded gamma scintillation detectors (2-in. by 2-in. thallium-activated sodium iodide probe) to identify areas of elevated radionuclide activity was performed. Near-surface gamma measurements taken using a cone-shielded gamma scintillation detector were also used in determining areas of surface contamination. Using the shielded detector ensured that the majority of the radiation detected by the instrument originated from the ground directly beneath the unit. Shielding against lateral gamma flux, or shine, from nearby areas of contamination minimized potential sources of error in the measurements. The measurements were taken 12 in. above the ground at the intersections of 10-ft grid lines. The shielded detector was calibrated at the Technical Measurements Center (TMC) in Grand Junction, Colorado, to provide a correlation of counts per minute (cpm) to picocuries per gram (pCi/g). This calibration demonstrated that 11,000 cpm corresponds to the DOE guideline of 5 pCi/g plus local average background of 1 pCi/g for thorium-232 in surface soils (Ref. 9).

A subsurface investigation was conducted to determine the depth to which the previously identified surface contamination extends and to

locate subsurface contamination where there is no surface manifestation. The subsurface characterization consisted of drilling and gamma logging 18 boreholes (Figure 4-1) using either a 3-in.- or 6-in.-diameter auger bit; holes were drilled to depths determined in the field by the radiological and geological support representatives.

The downhole gamma logging technique was used because the procedure can be completed more quickly than collecting soil samples, and it eliminates the need for analyzing these samples in a laboratory. A 2-in. by 2-in. sodium iodide gamma scintillation detector was used to perform the downhole logging. The instrument was calibrated at TMC where it was determined that a count rate of approximately 40,000 cpm corresponds to the 15-pCi/g subsurface contamination guideline for thorium-232 in subsurface soils. This relationship has also been corroborated in results from previous characterizations where thorium-232 was found (Ref. 9).

Gamma radiation measurements were taken at 6-in. vertical intervals, and determined the depth and concentration of the contamination. The gamma logging data were reviewed to identify trends, regardless of whether concentrations exceeded the guidelines.

4.1.2 Sample Collection and Analysis

To identify surface areas where the level of contamination exceeded the DOE guideline of 5 pCi/g for thorium-232 in surface soils, areas with measurements of more than 11,000 cpm were plotted. Using these data as well as data from previous surveys (Refs. 5, 6, 7, and 8), the locations of biased surface soil samples were selected to better define the limits of contamination. Surface soil samples were taken at 18 locations (Figure 4-2) and analyzed for thorium-232 and radium-226. Each sample was dried, pulverized, and counted for 10 min using an intrinsic germanium detector housed in a lead counting cave lined with cadmium and copper. The pulse height distribution was sorted using a computer-based, multichannel




FIGURE 4-1 BOREHOLE LOCATIONS AT 11 BRANCA COURT




FIGURE 4-2 SURFACE AND SUBSURFACE SOIL SAMPLING LOCATIONS AT 11 BRANCA COURT

analyzer. Radionuclide concentrations were determined by comparing the gamma spectrum of each sample with the spectrum of a certified counting standard for the radionuclide of interest.

Subsurface soil samples were collected from 18 locations (Figure 4-2) using the side wall sampling method and were analyzed to compare laboratory soil sample results to downhole gamma radiation measurements. A cup or can attached to a steel pipe or wooden stake was inserted into the borehole and used to scrape samples off the side of the borehole at a specified depth. The subsurface soil samples were analyzed for radium-226 and thorium-232 in the same manner as the surface soil samples.

4.2 BUILDING RADIOLOGICAL CHARACTERIZATION

After evaluating previous radiological survey data as well as data from this characterization, it was suspected that contamination might be present under the foundation of the residence. A radon measurement was obtained to verify the presence of contaminated material under the residence and to estimate potential occupational exposures during future remedial actions.

Indoor radon measurements were taken using the Tedlar bag technique. Using this method, radon measurements are obtained by pumping air into a Tedlar bag at a rate of approximately 2 l/min and transferring the air sample directly into a scintillation cell with an interior coating of zinc sulfide and an end window for viewing the scintillations. Analysis of the sample was simplified by allowing the radon decay products to build up over time. This method allows all the radon decay products to come into secular equilibrium with the radon. The scintillation cell was placed in contact with a photomultiplier tube, and the scintillations were counted using standard nuclear counting instrumentation.

Indoor air sample collection was also performed to determine working levels (WL) of radon daughters. Measurement of radon daughters was

done by collecting an air sample for exactly 5 min through a 0.45-micron membrane filter at a rate of 11 liters/min for a total sample volume of 55 l. Alpha particle activity on the filter paper was counted 40 to 90 min after sampling using an alpha scintillation detector coupled to a count-rate meter or a digital scaler.

5.0 CHARACTERIZATION RESULTS

5.1 FIELD RADIOLOGICAL CHARACTERIZATION

Near-surface gamma radiation measurements on the property ranged from 2,500 cpm to approximately 16,000 cpm. The average background level for this area is 5,000 cpm. A measurement of 11,000 cpm is approximately equal to the DOE guideline for thorium-232 of 5 pCi/g above background for surface soil contamination. Using this correlation, the near-surface gamma measurements were used to determine the extent of surface contamination as well as the basis for selecting the locations of soil samples.

Surface soil samples were taken from several locations on the property (Figure 4-2). These samples were analyzed for thorium-232 and radium-226. The concentrations in these samples ranged from 0.9 pCi/g to 11.3 pCi/g for thorium-232 and from 0.4 pCi/g to 2.0 pCi/g for radium-226. Analysis results for surface soils (depths from 0.0 to 0.5 ft) are provided in Table 5-1. Results showed concentrations of thorium-232 in excess of DOE guidelines (5 pCi/g plus background of 1 pCi/g for surface soils) with a maximum concentration of 11.3 pCi/g. Use of the "less than" ($<$) notation in reporting results indicates that the radionuclide was not present in concentrations that are quantitative with the instruments and techniques used. The "less than" value represents the lower bound of the quantitative capacity of the instrument and technique used and is based on various factors, including the volume, size, and weight of the sample; the type of detector used; the counting time, and the background count rate. The actual concentration of the radionuclide is less than the value indicated. In addition, since radioactive decay is a random process, a correlation between the rate of disintegration and a given radionuclide concentration cannot be precisely established. For this reason, the exact concentration of the radionuclide cannot be determined. As such, each value that can be quantitatively determined has an associated uncertainty term (\pm), which represents

the amount by which the actual concentration can be expected to differ from the value given in the table. The uncertainty term has an associated confidence level of 95 percent.

Analysis results for subsurface soil samples given in Table 5-1 (depths from 0.5 to 1.0 ft) are consistent with the gamma logging data in Table 5-2. The results in Table 5-2 showed a range from 6,000 cpm to 130,000 cpm. A measurement of 40,000 cpm is approximately equal to the DOE guideline for subsurface contamination of 15 pCi/g. Analyses of subsurface soil samples indicated thorium-232 concentrations ranging from 1.0 pCi/g to 9.4 pCi/g and radium-226 concentrations ranging from 0.5 to 2.0 pCi/g.

On the basis of near-surface gamma radiation measurements, surface soil sample analysis, and downhole gamma logging, contamination of this property is believed to consist of surface and subsurface contamination. Areas of surface contamination are shown in Figure 5-1. Subsurface contamination ranges from 1.0 to 8.5 ft in depth. In addition, subsurface contamination is suspected to exist beneath the aboveground pool in the backyard. Areas of subsurface contamination are shown in Figure 5-2.

The vertical and horizontal limits of contamination as determined by this characterization effort are being evaluated to determine the volume of contaminated material that will require remedial action. To develop this estimate, BNI will consider the location of the contamination, construction techniques, and safety procedures.

5.2 BUILDING RADIOLOGICAL CHARACTERIZATION

Results of two indoor radon measurements made with the Tedlar bag method indicated concentrations of 0.4 and 0.8 pCi/l. These measurements were substantially less than the applicable DOE guideline of 3.0 pCi/l (Ref. 10).





FIGURE 5-1 AREAS OF SURFACE CONTAMINATION AT 11 BRANCA COURT



22

FIGURE 5-2 AREAS OF SUBSURFACE CONTAMINATION AT 11 BRANCA COURT

Results of measurements for radon daughters ranged from 0.003 to 0.004 WL and were substantially less than the applicable generic guideline (40 CFR 192) (Ref. 10) of an annual average (or equivalent) radon decay product concentration not to exceed 0.02 WL. Measurements for thoron daughters yielded negligible results.

Exterior gamma measurements were not obtained because of restricted access to the property.

SURFACE AND SUBSURFACE RADIONUCLIDE CONCENTRATIONS IN SOIL
FOR 11 BRANCA COURT^a

Page 1 of 2

Coordinates		Depth (ft)	Concentration (pCi/g +/- 2 sigma)		
East	North		Uranium-238	Radium-226	Thorium-232
3523	2165	0.0 - 0.5	-b-	0.9 +/- 0.4	1.7 +/- 0.3
3523	2165	0.5 - 1.0	-b-	2.0 +/- 0.4	2.7 +/- 0.4
3540	2097	0.0 - 0.5	-b-	1.4 +/- 0.5	1.9 +/- 0.5
3540	2097	0.5 - 1.0	-b-	1.0 +/- 0.3	1.3 +/- 0.3
3541	2169	0.0 - 0.5	-b-	0.7 +/- 0.3	0.9 +/- 0.6
3541	2169	0.5 - 1.0	-b-	0.7 +/- 0.2	1.0 +/- 0.4
3543	2105	0.0 - 0.5	-b-	1.3 +/- 0.2	2.1 +/- 0.4
3543	2105	0.5 - 1.0	-b-	0.5 +/- 0.3	1.7 +/- 0.1
3550	2140	0.0 - 0.5	-b-	0.7 +/- 0.4	1.5 +/- 0.3
3550	2140	0.5 - 1.0	-b-	< 1.1	2.2 +/- 0.4
3554	2100	0.0 - 0.5	-b-	0.6 +/- 0.3	2.0 +/- 0.3
3554	2100	0.5 - 1.0	-b-	1.2 +/- 0.3	1.6 +/- 0.3
3557	2148	0.0 - 0.5	-b-	0.7 +/- 0.3	1.1 +/- 0.3
3557	2148	0.5 - 1.0	-b-	1.7 +/- 0.5	1.4 +/- 0.5
3563	2092	0.0 - 0.5	-b-	2.0 +/- 0.5	2.2 +/- 0.5
3563	2092	0.5 - 1.0	-b-	< 1.3	< 2.0
3563	2173	0.0 - 0.5	-b-	1.0 +/- 0.3	1.4 +/- 0.3
3563	2173	0.5 - 1.0	-b-	1.1 +/- 0.7	1.8 +/- 0.5

TABLE 5-1
(continued)

Page 2 of 2

Coordinates		Depth (ft)	Concentration (pCi/g +/- 2 sigma)		
East	North		Uranium-238	Radium-226	Thorium-232
3568	2172	0.0 - 0.5	-b-	0.9 +/- 0.4	1.3 +/- 0.4
3568	2172	0.5 - 1.0	-b-	1.6 +/- 0.7	1.8 +/- 0.9
3573	2156	0.0 - 0.5	-b-	0.4 +/- 0.3	1.5 +/- 0.3
3573	2156	0.5 - 1.0	-b-	1.1 +/- 0.6	1.4 +/- 0.4
3581	2141	0.0 - 0.5	-b-	< 1.8	6.1 +/- 0.7
3581	2141	0.5 - 1.0	-b-	0.8 +/- 0.3	1.9 +/- 0.2
3586	2093	0.0 - 0.5	-b-	0.7 +/- 0.4	2.1 +/- 0.3
3586	2093	0.5 - 1.0	-b-	1.1 +/- 0.3	1.5 +/- 0.3
3590	2173	0.0 - 0.5	-b-	1.4 +/- 0.3	1.0 +/- 0.5
3590	2173	0.5 - 1.0	-b-	0.5 +/- 0.4	2.5 +/- 0.3
3597	2113	0.0 - 0.5	-b-	0.8 +/- 0.3	1.6 +/- 0.4
3597	2113	0.5 - 1.0	-b-	< 1.2	1.8 +/- 0.3
3619	2121	0.0 - 0.5	-b-	0.7 +/- 0.5	4.4 +/- 0.5
3619	2121	0.5 - 1.0	-b-	< 1.2	3.3 +/- 0.5
3619	2147	0.0 - 0.5	-b-	< 1.5	5.2 +/- 0.6
3619	2147	0.5 - 1.0	-b-	0.8 +/- 0.3	5.6 +/- 0.7
3620	2167	0.0 - 0.5	-b-	< 1.9	11.3 +/- 0.9
3620	2167	0.5 - 1.0	-b-	0.9 +/- 0.4	9.4 +/- 0.5

^aSampling locations are shown in Figure 4-2.

^bAnalysis not requested.

TABLE 5-2
 DOWNHOLE GAMMA LOGGING RESULTS
 FOR 11 BRANCA COURT^a

Page 1 of 6

<u>Coordinates</u>		Depth ^b (ft)	Count Rate ^c (cpm)
East	North		

Borehole 388R^d

3568	2172	0.5	11000
3568	2172	1.0	11000
3568	2172	1.5	13000
3568	2172	2.0	13000
3568	2172	2.5	13000
3568	2172	3.0	13000

Borehole 389R^d

3573	2156	0.5	10000
3573	2156	1.0	11000
3573	2156	1.5	13000
3573	2156	2.0	14000
3573	2156	2.5	14000
3573	2156	3.0	18000
3573	2156	3.5	20000
3573	2156	4.0	21000
3573	2156	4.5	22000

Borehole 390R^d

3557	2148	0.5	14000
3557	2148	1.0	15000
3557	2148	1.5	15000
3557	2148	2.0	14000
3557	2148	2.5	16000
3557	2148	3.0	19000
3557	2148	3.5	17000
3557	2148	4.0	21000
3557	2148	4.5	22000
3557	2148	5.0	21000
3557	2148	5.5	19000
3557	2148	6.0	20000
3557	2148	6.5	23000
3557	2148	7.0	27000
3557	2148	7.5	26000
3557	2148	8.0	16000

Borehole 391R^d

3523	2165	0.5	9000
3523	2165	1.0	13000

TABLE 5-2
(continued)

Page 2 of 6

Coordinates		Depth ^b (ft)	Count Rate ^c (cpm)
East	North		
<u>Borehole 393R^d</u>			
3554	2100	0.5	13000
3554	2100	1.0	12000
3554	2100	1.5	12000
3554	2100	2.0	12000
3554	2100	2.5	13000
3554	2100	3.0	13000
3554	2100	3.5	17000
3554	2100	4.0	19000
3554	2100	4.5	20000
3554	2100	5.0	22000
3554	2100	5.5	18000
3554	2100	6.0	12000
3554	2100	6.5	9000
3554	2100	7.0	9000
3554	2100	7.5	8000
3554	2100	8.0	8000
<u>Borehole 394R</u>			
3540	2097	0.5	9000
3540	2097	1.0	11000
3540	2097	1.5	12000
3540	2097	2.0	12000
3540	2097	2.5	12000
3540	2097	3.0	13000
<u>Borehole 395R^d</u>			
3620	2167	0.5	40000
3620	2167	1.0	46000
3620	2167	1.5	53000
3620	2167	2.0	109000
3620	2167	2.5	29000
3620	2167	3.0	14000
3620	2167	3.5	11000
3620	2167	4.0	10000
3620	2167	4.5	8000
3620	2167	5.0	6000
3620	2167	5.5	7000
3620	2167	6.0	10000
3620	2167	6.5	10000
3620	2167	7.0	11000

TABLE 5-2
(continued)

Page 3 of 6

Coordinates		Depth ^b (ft)	Count Rate ^c (cpm)
East	North		
<u>Borehole 396R^d</u>			
3590	2173	0.5	9000
3590	2173	1.0	10000
<u>Borehole 397R^d</u>			
3581	2141	0.5	11000
3581	2141	1.0	10000
3581	2141	1.5	11000
3581	2141	2.0	15000
3581	2141	2.5	22000
3581	2141	3.0	35000
3581	2141	3.5	47000
3581	2141	4.0	86000
3581	2141	4.5	43000
3581	2141	5.0	23000
3581	2141	5.5	14000
3581	2141	6.0	10000
3581	2141	6.5	10000
3581	2141	7.0	7000
<u>Borehole 398R^d</u>			
3619	2147	0.5	29000
3619	2147	1.0	35000
3619	2147	1.5	41000
3619	2147	2.0	53000
3619	2147	2.5	32000
3619	2147	3.0	18000
3619	2147	3.5	12000
3619	2147	4.0	10000
3619	2147	4.5	10000
3619	2147	5.0	9000
3619	2147	5.5	7000
3619	2147	6.0	7000
<u>Borehole 399R^d</u>			
3619	2121	0.5	26000
3619	2121	1.0	34000
3619	2121	1.5	31000
3619	2121	2.0	17000
3619	2121	2.5	15000

TABLE 5-2
(continued)

Page 4 of 6

Coordinates		Depth ^b (ft)	Count Rate ^c (cpm)
East	North		

Borehole 399R (continued)^d

3619	2121	3.0	14000
3619	2121	3.5	12000
3619	2121	4.0	10000
3619	2121	4.5	10000
3619	2121	5.0	9000
3619	2121	5.5	7000
3619	2121	6.0	7000

Borehole 400R^d

3597	2113	0.5	11000
3597	2113	1.0	12000
3597	2113	1.5	18000
3597	2113	2.0	22000
3597	2113	2.5	20000
3597	2113	3.0	19000
3597	2113	3.5	19000
3597	2113	4.0	15000
3597	2113	4.5	20000
3597	2113	5.0	9000
3597	2113	5.5	9000
3597	2113	6.0	8000

Borehole 506R^d

3541	2169	0.5	14000
3541	2169	1.0	16000
3541	2169	1.5	16000
3541	2169	2.0	16000
3541	2169	2.5	16000
3541	2169	3.0	16000
3541	2169	3.5	17000
3541	2169	4.0	19000
3541	2169	4.5	25000
3541	2169	5.0	35000
3541	2169	5.5	79000
3541	2169	6.0	130000
3541	2169	6.5	84000
3541	2169	7.0	40000
3541	2169	7.5	33000
3541	2169	8.0	31000
3541	2169	8.5	33000

TABLE 5-2
(continued)

Page 5 of 6

Coordinates		Depth ^b (ft)	Count Rate ^c (cpm)
East	North		

Borehole 506R (continued)^d

3541	2169	9.0	19000
3541	2169	9.5	17000
3541	2169	10.0	17000

Borehole 507R

3543	2105	0.5	12000
3543	2105	1.0	13000
3543	2105	1.5	13000
3543	2105	2.0	15000
3543	2105	2.5	13000
3543	2105	3.0	15000
3543	2105	3.5	20000
3543	2105	4.0	26000
3543	2105	4.5	31000
3543	2105	5.0	36000
3543	2105	5.5	37000
3543	2105	6.0	34000
3543	2105	6.5	27000
3543	2105	7.0	16000
3543	2105	7.5	13000
3543	2105	8.0	12000
3543	2105	8.5	16000
3543	2105	9.0	14000
3543	2105	9.5	15000

Borehole 610R^d

3611	2093	0.5	11000
3611	2093	1.0	12000
3611	2093	1.5	12000
3611	2093	2.0	12000
3611	2093	2.5	12000
3611	2093	3.0	13000
3611	2093	3.5	13000
3611	2093	4.0	12000
3611	2093	4.5	13000
3611	2093	5.0	13000
3611	2093	5.5	12000
3611	2093	6.0	12000
3611	2093	6.5	12000
3611	2093	7.0	12000

TABLE 5-2
(continued)

Page 6 of 6

Coordinates		Depth ^b (ft)	Count Rate ^c (cpm)
East	North		
<u>Borehole 611R^d</u>			
3588	2092	0.5	12000
3588	2092	1.0	13000
3588	2092	1.5	14000
3588	2092	2.0	13000
3588	2092	2.5	12000
3588	2092	3.0	12000
3588	2092	3.5	13000
3588	2092	4.0	12000
3588	2092	4.5	11000
3588	2092	5.0	10000
3588	2092	5.5	11000

Borehole (unnumbered)^e

3550	2140	0.5	10000
3550	2140	1.0	12000

Borehole (unnumbered)^f

3563	2173	0.5	8000
3563	2173	1.0	10000
3563	2173	1.5	13000

^aBorehole locations are shown in Figure 4-1.

^bThe variations in depths of boreholes and corresponding results given in this table are based on the boreholes penetrating the contamination or the drill reaching refusal.

^cInstrument used was 2-in. by 2-in. thallium-activated sodium iodide gamma scintillation detector.

^dBottom of borehole collapsed.

^eNo borehole number assigned (refusal at 1 ft).

^fNo borehole number assigned (refusal at 1.5 ft).

REFERENCES

1. U.S. Department of Energy. Description of the Formerly Utilized Sites Remedial Action Program, ORO-777, Oak Ridge, TN, September 1980 (as modified by DOE in October 1983).
2. Argonne National Laboratory. Action Description Memorandum, Interim Remedial Actions at Maywood, New Jersey, Argonne, IL, March 1987.
3. Argonne National Laboratory. Action Description Memorandum, Proposed 1984 Remedial Actions at Maywood, New Jersey, Argonne, IL, June 8, 1984.
4. Bechtel National, Inc. Post-Remedial Action Report for the Lodi Residential Properties, DOE/OR/20722-89, Oak Ridge, TN, August 1986.
5. NUS Corporation. Radiological Study of Maywood Chemical, Maywood, New Jersey, November 1983.
6. EG&G Energy Measurements Group. An Aerial Radiologic Survey of the Stepan Chemical Company and Surrounding Area, Maywood, New Jersey, NRC-8109, Oak Ridge, TN, September 1981.
7. Oak Ridge National Laboratory. Results of the Mobile Gamma Scanning Activities in Lodi, New Jersey, ORNL/RASA-84/3, Oak Ridge, TN, October 1984.
8. Oak Ridge National Laboratory. Results of the Radiological Survey at 11 Branca Court (LJ043), Lodi, New Jersey, ORNL/RASA-86/35, Oak Ridge, TN, September 1986.
9. Letter, Jeff Brown, Thermo Analytical/Eberline, to Distribution. "Technical Review of Grand Junction Instrument Correlation Study," BNI CCN 035506, March 17, 1986.

10. U.S. Code of Federal Regulations. 40 CFR 192, "Health and Environmental Protection Standards for Uranium and Thorium Mill Tailings, " Washington, D.C., July 1986.

APPENDIX A

GEOLOGIC DRILL LOGS FOR 11 BRANCA COURT

LODI, NEW JERSEY

GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
11 Branca Ct. LODI				N 2172; E 3568		14501-138	1 OF 1	388R				
BEGUN		COMPLETED	DRILLER		DRILL MAKE AND MODEL		SIZE	OVERBURDEN	ROCK (FT.)	TOTAL DEPTH		
10-3-86		10-3-86	MORETRENCH		B&S little beaver		4"	4.0		4.0		
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK				
/					43.4	/		/				
SAMPLE HAMMER WEIGHT/FALL			CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:						
N/A			NONE			D. MCGRANE						
SAMP. TYPE AND DIAM.	SAMP. ADV. LEN. CORE	SAMPLE REC. CORE REC.	SAMPLE BLOWS "N" X CORE RECOVERY	WATER PRESSURE TESTS			ELEV.	DEPTH	GRAPHICS	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON: WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOSS IN G.P.M.	PRESS. P.S.I.	TIME IN MIN.						
							43.4					
							39.4				0.0 - 4.0 FT. SILTY SAND (SM) . Color stratified; fine to medium grained; soft; numerous rounded and angular pebbles and gravel of mixed lithologies (difficult drilling); poorly consolidated (loose); numerous grass roots and organics; moist. 0.0-0.3 ft., moderate brown (5 YR 3/4); garden soil. 0.3-4.0 FT., dark reddish brown, (10 R 3/4).	Borehole drilled 0 - 4.0 ft. using 4" solid-stem augers.
											Bottom of boring at 4.0 FT. Borehole backfilled with auger spoils, 10-3-86. NOTE: Did not penetrate below disturbed soils; auger refusal.	Site checked for radioactive contamination and hole gamma-logged by Eberline-TMA, Corp. No ground water observed.
												Auger refusal at 4.0 ft. Cobble?
												Description and classification of soil samples by visual examination.
SS = SPLIT SPOON; ST = SHELBY TUBE; D = DENNISON; P = PITCHER; O = OTHER										SITE		HOLE NO.
11 Branca Ct. LODI										388R		

GEOLOGIC DRILL LOG				PROJECT FUSRAP		JOB NO. 14501-138	SHEET NO. 1 OF 1	HOLE NO. 389R				
SITE 11 Branca Ct. LODI			COORDINATES N 2156; E 3573			ANGLE FROM HORIZ Vertical		BEARING -----				
BEGUN 10-3-86	COMPLETED 10-3-86	DRILLER MORETRENCH	DRILL MAKE AND MODEL B&S little beaver	SIZE 4"	OVERBURDEN 6.0	ROCK (FT.)	TOTAL DEPTH 6.0					
CORE RECOVERY (FT./%) /		CORE BOXES	SAMPLES	EL. TOP CASING	GROUND EL. 43.7	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK				
SAMPLE HAMMER WEIGHT/FALL N/A		CASING LEFT IN HOLE: DIA./LENGTH NONE			LOGGED BY: D. MCGRANE							
SAMP. TYPE AND DIAM.	SAMP. ADV. LEN. CORE	SAMPLE REC. CORE REC.	SAMPLE BLOWS "N" X CORE RECOVERY	WATER PRESSURE TESTS			ELEV.	DEPTH	GRAPHICS	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON: WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOSS IN G.P.M.	PRESS. P.S.I.	TIME IN MIN.						
							43.7					
							37.7	5	5		<p>0.0 - 6.0 FT. SILTY SAND (SM-SC). Fill and natural material; color stratified; fine to medium grained; soft; poorly consolidated (loose); moist. 0.0-0.5 ft., moderate brown (5 YR 3/4); garden soil. 0.5-5.0 FT., dark reddish brown, (10 R 3/4). A few pieces of black carboniferous gravel, sandstone gravel and glass (fill). 5.0-5.2 FT. Pale green (5 YG 7/2), and mottled dark yellowish orange (10 YR 6/6); clayey (SC). 5.2-6.0 FT. Dark reddish brown.</p> <p>Bottom of boring at 6.0 FT. Borehole backfilled with auger spoils, 10-3-86. NOTE: Unable to determine if auger penetrated below disturbed soils; auger refusal.</p>	<p>Borehole drilled 0 - 6.0 ft. using 4" solid-stem augers.</p> <p>Site checked for radioactive contamination and hole gamma-logged by Eberline-TMA, Corp. No ground water observed.</p> <p>Auger refusal at 6.0 ft. Cobble?</p>
												Description and classification of soil samples by visual examination.

SS = SPLIT SPOON; ST = SHELBY TUBE;
D = DENNISON; P = PITCHER; O = OTHER

SITE
11 Branca Ct. LODI

HOLE NO.
389R

GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
				FUSRAP		14501-138	1 OF 1	390R				
SITE			COORDINATES			ANGLE FROM HORIZ		BEARING				
11 Branca Ct. LODI			N 2148; E 3557			Vertical		-----				
BEGUN	COMPLETED	DRILLER	DRILL MAKE AND MODEL		SIZE	OVERBURDEN	ROCK (FT.)	TOTAL DEPTH				
10-3-86	10-3-86	MORETRENCH	B&S little beaver		4"	9.0		9.0				
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK				
					43.8	8.0/35.8 10-3-86						
SAMPLE HAMMER WEIGHT/FALL			CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:						
N/A			NONE			D. MCGRANE						
SAMP. TYPE AND DIAM.	SAMP. ADV. LEN CORE	SAMP. REC. CORE REC.	SAMPLE BLOWS "N" % CORE RECOVERY	WATER PRESSURE TESTS			ELEV.	DEPTH	GRAPHICS	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON: WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOSS IN G.P.M.	PRESS. P.S.I.	TIME IN MIN.						
							43.8					
								5			0.0 - 9.0 FT. <u>SILTY SAND (SM-SC)</u> . Color stratified; fine to medium grained; soft; poorly consolidated (loose); moist - saturated at 8.0 ft. 0.0-5.0 FT., dark reddish brown, (10 R 3/4).	Borehole drilled 0 - 9.0 ft. using 4" solid-stem augers.
							34.8				5.0-5.2 FT. Clayey seam (SC); mottled pale green (5 G 7/2), dark yellowish orange (10 YR 6/6), and grayish black (N2). 5.2-6.0 FT., dark reddish brown. 6.0-7.0 FT., moderate brown. 7.0-9.0 FT., dark reddish brown.	Site checked for radioactive contamination and hole gamma-logged by Eberline-TMA, Corp. Ground water observed, 10-3-86.
											Bottom of boring at 9.0 FT. Borehole backfilled with auger spoils, 10-3-86.	
											Description and classification of soil samples by visual examination.	
SS = SPLIT SPOON; ST = SHELBY TUBE; D = DENNISON; P = PITCHER; O = OTHER											SITE	HOLE NO.
											11 Branca Ct. LODI	390R

GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.					
				FUSRAP		14501-138	1 OF 1	391R					
SITE			COORDINATES			ANGLE FROM HORIZ		BEARING					
11 Branca Ct. LODI			N 2165; E 3523			Vertical		-----					
BEGUN	COMPLETED	DRILLER	DRILL MAKE AND MODEL	SIZE	OVERBURDEN	ROCK (FT.)	TOTAL DEPTH						
10-3-86	10-3-86	MORETRENCH	B&S little beaver	4"	2.0		2.0						
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP CASING	GROUND EL.	DEPTH/EL. GROUND WATER	DEPTH/EL. TOP OF ROCK						
/					44.4	7	/						
SAMPLE HAMMER WEIGHT/FALL		CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:								
N/A		NONE			D. MCGRANE								
SAMP. TYPE AND DIAM.	SAMP. ADV. LEN CORE	SAMPLE REC. CORE REC.	SAMPLE BLOWS "N"	% CORE RECOVERY	WATER PRESSURE TESTS			ELEV.	DEPTH	GRAPHICS	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON: WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					LOSS IN G.P.M.	PRESS. P.S.I.	TIME IN MIN.						
								44.4					
								44.1				0.0 - 0.3 FT. RIVER ROCK 2" diam.	Borehole drilled 0 - 2.0 ft. using 4" solid-stem augers.
								42.4				0.3 - 2.0 FT. SILTY SAND (SM). Fill material; dark reddish brown, (10 R 3/4); fine to medium grained with numerous pieces of gravel and cobbles of mixed lithology; soft; unconsolidated; moist.	
												Bottom of boring at 2.0 FT. Borehole backfilled with auger spoils, 10-3-86.	Site checked for radioactive contamination and hole gamma-logged by Eberline-TMA, Corp. No ground water observed.
													Auger refusal at 2.0 ft. Cobble?
													Description and classification of soil samples by visual examination.
SS = SPLIT SPOON; ST = SHELBY TUBE; D = DENNISON; P = PITCHER; O = OTHER											SITE		HOLE NO.
											11 Branca Ct. LODI		391R

GEOLOGIC DRILL LOG										PROJECT		JOB NO.		SHEET NO.		HOLE NO.	
SITE										COORDINATES				ANGLE FROM HORIZ		BEARING	
11 Branca Ct. LODI										N 2100; E 3554				Vertical		-----	
BEGUN		COMPLETED		DRILLER		DRILL MAKE AND MODEL		SIZE		OVERBURDEN		ROCK (FT.)		TOTAL DEPTH			
10-3-86		10-3-86		MORETRENCH		B&S little beaver		4"		9.0				9.0			
CORE RECOVERY (FT./%)			CORE BOXES		SAMPLES		EL. TOP CASING		GROUND EL.		DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK				
/									44.9		8.0/36.9 10-3-86		/				
SAMPLE HAMMER WEIGHT/FALL				CASING LEFT IN HOLE: DIA./LENGTH				LOGGED BY:									
N/A				NONE				D. MCGRANE									
SAMP. TYPE AND DIAM.	SAMP. ADV. LEN CORE	SAMP. REC. CORE REC.	SAMP. BLOWS "N" % CORE RECOVERY	WATER PRESSURE TESTS			ELEV.	DEPTH	GRAPHICS	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON: WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.					
				LOSS IN G.P.M.	PRESS. P.S.I.	TIME IN MIN.											
							44.9				<p>0.0 - 9.0 FT. SILTY SAND (SM-SC). Fill and natural material; color stratified; fine to medium grained; soft; poorly consolidated (loose); moist - saturated at 8.0 ft.</p> <p>0.0-5.0 FT., dark reddish brown, (10 R 3/4). A few blocks and pieces of sandstone gravel; piece of glass at 4 ft.; fill?</p> <p>5.0-6.5 FT., grayish black (N2); clayey (SC); numerous organics; residual floodplain sediments?</p> <p>6.5 - 7.0 FT., pale green (5 G 7/2); clayey (SC).</p> <p>7.0-9.0 FT., dusky red (5 R 3/4).</p>	<p>Borehole drilled 0 - 9.0 ft. using 4" solid-stem augers.</p> <p>Site checked for radioactive contamination and hole gamma-logged by Eberline-TMA, Corp. Ground water observed, 10-3-86.</p>					
							35.9				<p>Bottom of boring at 9.0 FT. Borehole backfilled with auger spoils, 10-3-86.</p>	<p>Description and classification of soil samples by visual examination.</p>					

SS = SPLIT SPOON; ST = SHELBY TUBE; D = DENNISON; P = PITCHER; O = OTHER

SITE

11 Branca Ct. LODI

HOLE NO.

393R

GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
				FUSRAP		14501-138	1 OF 1	394R				
SITE			COORDINATES			ANGLE FROM HORIZ		BEARING				
11 Branca Ct. LODI			N 2097; E 3540			Vertical		-----				
BEGUN	COMPLETED	DRILLER		DRILL MAKE AND MODEL		SIZE	OVERBURDEN	ROCK (FT.)	TOTAL DEPTH			
10-3-86	10-3-86	MORETRENCH		B&S little beaver		4"	3.5		3.5			
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK				
					44.5							
SAMPLE HAMMER WEIGHT/FALL			CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:						
N/A			NONE			D. MCGRANE						
SAMP. TYPE AND DIAM.	SAMP. ADV. LEN CORE	SAMPLE REC. CORE REC.	SAMPLE BLOWS "N" % CORE RECOVERY	WATER PRESSURE TESTS			ELEV.	DEPTH	GRAPHICS	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON: WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOSS IN G.P.M.	PRESS. P.S.I.	TIME IN MIN.						
							44.5					
							41.0				<p>0.0 - 3.5 FT. SILTY SAND (SM). Fill material?; color stratified; fine to medium grained with few pieces of gravel and cobbles of mixed lithology; soft; unconsolidated; moist.</p> <p>0.0-2.5 FT., dark reddish brown, (10 R 3/4);</p> <p>2.5-3.5 FT., moderate brown (5 YR 3/4).</p>	<p>Borehole drilled 0 - 3.5 ft. using 4" solid-stem augers.</p>
											<p>Bottom of boring at 3.5 FT. Borehole backfilled with auger spoils, 10-3-86.</p>	<p>Site checked for radioactive contamination and hole gamma-logged by Eberline-TMA, Corp. No ground water observed.</p> <p>Auger refusal at 3.5 ft. Cobble?</p>
												<p>Description and classification of soil samples by visual examination.</p>

SS = SPLIT SPOON; ST = SHELBY TUBE; D = DENNISON; P = PITCHER; O = OTHER

SITE
11 Branca Ct. LODI

HOLE NO.
394R

GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.			
				FUSRAP		14501-138	1 OF 1	395R			
SITE			COORDINATES			ANGLE FROM HORIZ BEARING					
11 Branca Ct. LODI			N 2167; E 3620			Vertical -----					
BEGUN	COMPLETED	DRILLER		DRILL MAKE AND MODEL		SIZE	OVERBURDEN	ROCK (FT.)	TOTAL DEPTH		
10-3-86	10-3-86	MORETRENCH		B&S little beaver		4"	9.0		9.0		
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK			
/					43.3	6.5/36.8 10-3-86		/			
SAMPLE HAMMER WEIGHT/FALL		CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:						
N/A		NONE			D. MCGRANE						
SAMP. TYPE AND DIAM.	SAMP. ADV. LEN CORE	SAMP. REC. CORE REC.	SAMPLE BLOWS "N" % CORE RECOVERY	WATER PRESSURE TESTS			ELEV.	DEPTH	GRAPHICS SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON: WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOSS IN G.P.M	PRESS. P.S.I.	TIME IN MIN.					
							43.3			0.0 - 9.0 FT. SILTY SAND (SM-SC) . Fill and natural material; color stratified; fine to medium grained with numerous sub-rounded pebbles of mixed lithologies; soft; poorly consolidated (loose); moist - saturated at 6.5 ft. 0.0-3.0 FT., dark reddish brown, (10 R 3/4). Numerous grass roots and organics at surface. 3.0-5.0 FT., clayey zone (SC); mottled grayish black (N2), pale green (5 G 7/2), gray (N5), and dark yellowish orange (10 YR 6/6). 5.0-9.0 FT., dark yellowish orange.	Borehole drilled 0 - 9.0 ft. using 4" solid-stem augers. Site checked for radioactive contamination and hole gamma-logged by Eberline-TMA, Corp. Ground water observed, 10-3-86.
							34.3			Bottom of boring at 9.0 FT. Borehole backfilled with auger spoils, 10-3-86.	Description and classification of soil samples by visual examination.

SS = SPLIT SPOON; ST = SHELBY TUBE;
D = DENNISON; P = PITCHER; O = OTHER

SITE

11 Branca Ct. LODI

HOLE NO. 395R

GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
				FUSRAP		14501-138	1 OF 1	396R				
SITE			COORDINATES			ANGLE FROM HORIZ		BEARING				
11 Branca Ct. LODI			N 2173; E 3590			Vertical		-----				
BEGUN	COMPLETED	DRILLER	DRILL MAKE AND MODEL	SIZE	OVERBURDEN	ROCK (FT.)	TOTAL DEPTH					
10-3-86	10-3-86	MORETRENCH	B&S little beaver	4"	2.5		2.5					
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP CASING	GROUND EL.	DEPTH/EL. GROUND WATER	DEPTH/EL. TOP OF ROCK					
/					43.3	↓ /	/					
SAMPLE HAMMER WEIGHT/FALL		CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:							
N/A		NONE			D. MCGRANE							
SAMP. TYPE AND DIAM.	SAMP. ADV. LEN CORE	SAMPLE REC. CORE REC.	SAMPLE BLOWS "N" % CORE RECOVERY	WATER PRESSURE TESTS			ELEV.	DEPTH	GRAPHICS	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON: WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOSS IN G.P.M.	PRESS. P.S.I.	TIME IN MIN.						
							43.3					
							40.8				0.0 - 2.5 FT. SILTY SAND (SM) . Fill material; color stratified; fine to medium grained; numerous pieces of gravel and cobbles of mixed lithology; soft; unconsolidated; moist. 0.0-0.3 FT., moderate brown (5 YR 3/4); numerous grass roots and organics. 0.3-2.5 FT., dark reddish brown, (10 R 3/4).	Borehole drilled 0 - 2.5 ft. using 4" solid-stem augers.
											Bottom of boring at 2.5 FT. Borehole backfilled with auger spoils, 10-3-86.	Site checked for radioactive contamination and hole gamma-logged by Eberline-TMA, Corp. No ground water observed.
												Description and classification of soil samples by visual examination.
SS = SPLIT SPOON; ST = SHELBY TUBE; D = DENNISON; P = PITCHER; O = OTHER										SITE		
										11 Branca Ct. LODI		HOLE NO. 396R

GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.					
11 Branca Ct. LODI				FUSRAP		14501-138	1 OF 1	397R					
SITE			COORDINATES			ANGLE FROM HORIZ		BEARING					
11 Branca Ct. LODI			N 2141; E 3581			Vertical		-----					
BEGUN	COMPLETED	DRILLER	DRILL MAKE AND MODEL	SIZE	OVERBURDEN	ROCK (FT.)	TOTAL DEPTH						
10-3-86	10-3-86	MORETRENCH	B&S little beaver	4"	9.0		9.0						
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP CASING	GROUND EL.	DEPTH/EL. GROUND WATER	DEPTH/EL. TOP OF ROCK						
/					43.4	7.5/35.9 10-3-86	/						
SAMPLE HAMMER WEIGHT/FALL		CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:								
N/A		NONE			D. MCGRANE								
SAMP. TYPE AND DIAM.	SAMP. ADV. LEN CORE	SAMPLE REC. CORE REC.	SAMPLE BLOWS "N" % CORE RECOVERY	WATER PRESSURE TESTS			ELEV.	DEPTH	GRAPHICS	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON: WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.	
				LOSS IN G.P.M.	PRESS. P.S.I.	TIME IN MIN.							
							43.4				0.0 - 9.0 FT. SILTY SAND (SM-SC). Fill and natural material; color stratified; fine to medium grained; soft; poorly consolidated (loose); moist - saturated at 7.5 ft. 0.0-4.5 FT., moderate brown, (5 YR 3/4); few organics.	Borehole drilled 0 - 9.0 ft. using 4" solid-stem augers.	
								5			4.5-6.5 FT., clayey (SC); grayish black (N2) with a few pale green (5 G 7/2) lenses; floodplain sediments?.	Site checked for radioactive contamination and hole gamma-logged by Eberline-TMA, Corp.	
							34.4				6.5-9.0 FT., mottled moderate brown and dark reddish brown (10 R 3/4).	Ground water observed, 10-3-86.	
											Bottom of boring at 9.0 FT. Borehole backfilled with auger spoils, 10-3-86.		
											Description and classification of soil samples by visual examination.		
SS = SPLIT SPOON; ST = SHELBY TUBE; D = DENNISON; P = PITCHER; O = OTHER											SITE	11 Branca Ct. LODI	HOLE NO. 397R

GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
				FUSRAP		14501-138	1 OF 1	398R				
SITE			COORDINATES			ANGLE FROM HORIZ		BEARING				
11 Branca Ct. LODI			N 2147; E 3619			Vertical		-----				
BEGUN	COMPLETED	DRILLER	DRILL MAKE AND MODEL		SIZE	OVERBURDEN	ROCK (FT.)	TOTAL DEPTH				
10-3-86	10-3-86	MORETRENCH	B&S little beaver		4"	9.0		9.0				
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK				
/					41.7	7.0/34.7 10-3-86		/				
SAMPLE HAMMER WEIGHT/FALL			CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:						
N/A			NONE			D. MCGRANE						
SAMP. TYPE AND DIAM.	SAMP. ADV. LEN CORE	SAMP. REC. CORE REC.	SAMPLE BLOWS "N" % CORE RECOVERY	WATER PRESSURE TESTS			ELEV.	DEPTH	GRAPHICS	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON: WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOSS IN G.P.M.	PRESS. P.S.I.	TIME IN MIN.						
							41.7					
							32.7				0.0 - 9.0 FT. SILTY SAND (SM-SC). Fill and natural material; color stratified; fine to medium; soft; poorly consolidated (loose); moist - saturated at 7.0 ft. 0.0-0.5 FT., moderate brown, (5 YR 3/4). Numerous roots and organics. 0.5-2.0 FT., dark reddish brown (10 R 3/4). 2.0-4.0 FT., clayey (SC); grayish black (N2); floodplain sediments? 4.0-4.5 FT., pale green (5 G 7/2); clayey (SC); floodplain sediments? 4.5-5.0 FT., darkish yellow brown (10 YR 4/2). 5.0-9.0 FT., mottled moderate brown and dark reddish brown.	Borehole drilled 0 - 9.0 ft. using 4" solid-stem augers. Site checked for radioactive contamination and hole gamma-logged by Eberline-TMA, Corp. Ground water observed, 10-3-86.
											Bottom of boring at 9.0 FT. Borehole backfilled with auger spoils, 10-3-86.	Description and classification of soil samples by visual examination.
SS = SPLIT SPOON; ST = SHELBY TUBE; D = DENNISON; P = PITCHER; O = OTHER											SITE	HOLE NO.
											11 Branca Ct. LODI	398R

GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.						
11 Branca Ct. LODI				N 2121; E 3619		14501-138	1 OF 1	399R						
SITE		COORDINATES				ANGLE FROM HORIZ		BEARING						
11 Branca Ct. LODI		N 2121; E 3619				Vertical		-----						
BEGUN	COMPLETED	DRILLER		DRILL MAKE AND MODEL		SIZE	OVERBURDEN	ROCK (FT.)	TOTAL DEPTH					
10-3-86	10-3-86	MORETRENCH		B&S little beaver		4"	9.0		9.0					
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK						
/					41.4	8.0/33.4 10-3-86		/						
SAMPLE HAMMER WEIGHT/FALL			CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:								
N/A			NONE			D. MCGRANE								
SAMP. TYPE AND DIAM.	SAMP. ADV. LEN CORE	SAMPLE REC. CORE REC.	SAMPLE BLOWS "N" X CORE RECOVERY	WATER PRESSURE TESTS			ELEV.	DEPTH	GRAPHICS	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON: WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.		
				LOSS IN G.P.M	PRESS. P.S.F.	TIME IN MIN.								
							41.4				0.0 - 9.0 FT. SILTY SAND (SM-SC) . Fill and natural material; color stratified; fine to medium; soft; poorly consolidated (loose); moist - saturated at 8.0 ft. 0.0-0.5 FT., moderate brown, (5 YR 3/4). Numerous roots and organics. 0.5-2.0 FT., dark reddish brown (10 R 3/4). 2.0-4.0 FT., clayey (SC); grayish black (N2); floodplain sediments? 4.0-4.5 FT., gray (N5); clayey (SC). 4.5-9.0 FT., mottled moderate brown and dark reddish brown, and dark yellowish brown (10 YR 4/2).	Borehole drilled 0 - 9.0 ft. using 4" solid-stem augers. Site checked for radioactive contamination and hole gamma-logged by Eberline-TMA, Corp. Ground water observed, 10-3-86.		
							32.4				Bottom of boring at 9.0 FT. Borehole backfilled with auger spoils, 10-3-86.	Description and classification of soil samples by visual examination.		
SS = SPLIT SPOON; ST = SHELBY TUBE; D = DENNISON; P = PITCHER; O = OTHER											SITE	11 Branca Ct. LODI	HOLE NO.	399R

GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
				FUSRAP		14501-138	1 OF 1	400R				
SITE			COORDINATES			ANGLE FROM HORIZ		BEARING				
11 Branca Ct. (LODI)			N 2113; E 3597			Vertical		-----				
BEGUN	COMPLETED	DRILLER	DRILL MAKE AND MODEL		SIZE	OVERBURDEN	ROCK (FT.)	TOTAL DEPTH				
10-6-86	10-6-86	MORETRENCH	B&S Little Beaver		4"	9.0		9.0				
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK				
/					42.3	8.0/34.3 10-6-86		/				
SAMPLE HAMMER WEIGHT/FALL			CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:						
N/A			NONE			D. McGRANE						
SAMP. TYPE AND DIAM.	SAMP. ADU. LEN CORE	SAMP. REC. CORE REC.	SAMP. BLOWS "N" X CORE RECOVERY	WATER PRESSURE TESTS			ELEV.	DEPTH	GRAPHICS	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON: WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOSS IN G.P.M	PRESS. P.S.I.	TIME IN MIN.						
							42.3				0.0-9.0 ft. SILTY SAND (SM-SC) . Fill and natural material; fine-to medium-grained; soft; poorly consolidated (loose); moist; saturated at 8.0 ft. 0.0-4.5 ft. moderate brown (5YR3/4); mottled dark reddish brown (10R3/4); numerous organics; grass roots (0.0-0.5 ft.); few pebbles of various lithologies; fill? 4.5-6.0 ft. grayish black(N2); clayey (SC); few rounded pebbles; floodplain sediments? 6.0-9.0 ft. mottled moderate brown and dark reddish brown.	Borehole drilled 0.0-9.0 ft. using 4" solid-stem augers. Site checked for radioactive contamination and hole gamma-logged by Eberline-TMA, Corporation.
							33.3				Bottom of borehole at 9.0 ft. Auger spoils were immediately placed in the hole, 10-7-86.	8.0 ft. ground water observed.
												Description and classification of soil samples by visual examination.

SS = SPLIT SPOON; ST = SHELBY TUBE; SITE
D = DENNISON; P = PITCHER; O = OTHER

11 Branca Ct. (LODI)

HOLE NO. 400R

GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.			
				FUSRAP		14501-138	1 OF 1	506R			
SITE			COORDINATES			ANGLE FROM HORIZ		BEARING			
11 Branca Court (LODI)			N 2169; E 3541			Vertical		-----			
BEGUN	COMPLETED	DRILLER	DRILL MAKE AND MODEL		SIZE	OVERBURDEN	ROCK (FT.)	TOTAL DEPTH			
10-31-86	10-31-86	MORETRENCH	Mobile B-33		6"	11.0	3.0	14.0			
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK			
/					44.0	7.5/36.5 10-31-86		11.0/33.0			
SAMPLE HAMMER WEIGHT/FALL		CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:						
N/A		NONE			D. McGRANE						
SAMP. TYPE AND DIAM.	SAMP. ADJ. LEN CORE	SAMP. REC. CORE REC.	SAMPLE BLOWS "N" % CORE RECOVERY	WATER PRESSURE TESTS			ELEV.	DEPTH	GRAPHICS SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON: WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOSS IN G.P.M.	PRESS. P.S.I.	TIME IN MIN.					
							44.0			0.0-11.0 ft. SILTY SAND (SM) . Fill (0.0-6.5 ft.) and indigenous material (6.5-14.0 ft.); color stratified; fine-to medium-grained; with few-numerous pieces of rounded angular gravel (and occasional cobble) of various lithologies in the fill material; soft; unconsolidated (loose); sometimes clayey (SC-OH); moist-saturated at 7.5 ft. 0.0-0.3 ft. moderate brown (5YR3/4); numerous grass roots and organics. 0.3-6.5 ft. dark reddish brown; gravelly (0.3-3.5 ft.). 6.5-8.0 ft. grayish black (N2); clayey; numerous organics; stream sediments? 8.0-11.0 ft. dark yellowish brown (10YR4/2); decomposed sandstone?	Borehole drilled 0.0-14.0 ft. using 6" hollow-stem augers. Site checked for radioactive contamination and hole gamma-logged by Eberline-TMA, Corporation. 7.5 ft. ground water observed.
							33.0			11.0-14.0 ft. SANDSTONE . Dark reddish brown (10R3/4); fine grained (argillaceous); soft-moderately hard.	
							30.0			Bottom of borehole at 14.0 ft. Auger spoils were immediately replaced in the hole, 10-31-86.	
										Description and classification of soil samples by visual examination.	
SS = SPLIT SPOON; ST = SHELBY TUBE; D = DENNISON; P = PITCHER; O = OTHER								SITE		HOLE NO.	
11 Branca Court (LODI)										506R	

GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
				FUSRAP		14501-138	1 OF 1	507R				
SITE			COORDINATES			ANGLE FROM HORIZ		BEARING				
11 Branca Court (LODI)			N 2105; E 3543			Vertical		-----				
BEGUN	COMPLETED	DRILLER		DRILL MAKE AND MODEL		SIZE	OVERBURDEN	ROCK (FT.)				
10-31-86	10-31-86	MORETRENCH		Mobile B-33		6"	10.0					
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK				
/					44.7	7.5/37.2 10-31-86		/				
SAMPLE HAMMER WEIGHT/FALL			CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:						
N/A			NONE			D. McGRANE						
SAMP. TYPE AND DIAM.	SAMP. ADV. LEN CORE	SAMP. REC. CORE REC.	SAMP. BLOWS "N" % CORE RECOVERY	LOSS IN IN G.P.M	WATER PRESSURE TESTS		ELEV.	DEPTH	GRAPHICS	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON: WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
					PRESS. P.S.I.	TIME IN MIN.						
							44.7					
								5			0.0-10.0 ft. SILTY SAND (SM) . Fill (0.0-4.0 ft.) and indigenous material (4.0-10.0 ft.); color stratified; fine-to medium-grained; with few-numerous pieces of rounded angular gravel (and occasional cobble) of various lithologies in the fill material; soft; unconsolidated (loose); sometimes clayey (SC-OH); moist-saturated at 7.5 ft. 0.0-0.3 ft. moderate brown (5YR3/4); numerous grass roots and organics. 0.3-4.0 ft. dark reddish brown (10R3/4). 4.0-6.0 ft. moderate brown (5YR3/4), mottled grayish black (N2); mixed stream sediments and buried upper soil horizon? 6.0-10.0 ft. dark yellowish brown (10YR4/2); decomposed sandstone?	Borehole drilled 0.0-10.0 ft. using 6" hollow-stem augers. Site checked for radioactive contamination and hole gamma-logged by Eberline-TMA, Corporation. 7.5 ft. ground water observed.
							34.7	10			Bottom of borehole at 10.0 ft. Auger spoils were immediately replaced in the hole, 10-31-86.	
											Description and classification of soil samples by visual examination.	
SS = SPLIT SPOON; ST = SHELBY TUBE; D = DENNISON; P = PITCHER; O = OTHER											SITE	HOLE NO.
11 Branca Court (LODI)											507R	

GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
11 Branca Court (LODI)				N 2093; E 3611		14501-138	1 OF 1	610R				
BEGUN		COMPLETED	DRILLER	DRILL MAKE AND MODEL		SIZE	OVERBURDEN	ROCK (FT.)	TOTAL DEPTH			
10-6-86		10-6-86	Moretrench	B&S Little Beaver		4"	9.0		9.0			
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK				
/					41.5	8.5/33.0 10-6-86		/				
SAMPLE HAMMER WEIGHT/FALL			CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:						
N/A			None			D.McGrane						
SAMP. TYPE AND DIAM.	SAMP. ADV. LEN. CORE	SAMPLE REC. CORE REC.	SAMPLE BLOWS "N" X CORE RECOVERY	WATER PRESSURE TESTS			ELEV.	DEPTH	GRAPHICS	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON: WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOSS IN G.P.M.	PRESS. P.S.I.	TIME IN MIN.						
							41.5					
											0.0-9.0 ft. SILTY SAND (SM-SC) . Color stratified; fine-to medium-grained; soft; poorly consolidated (loose); dry-saturated at 8.5 ft. 0.0-0.5 ft. moderate brown (5YR3/4); numerous grass roots and organics; dry. 0.5-3.0 ft. dark yellowish brown (10YR4/2). 3.0-3.7 ft., dark reddish brown (10R3/4); few pieces of sandstone gravel. 3.7-4.0 ft., pale green (5G7/2); clayey (SC); moist. 4.0-9.0 ft., dark reddish brown; few rounded-angular pebbles of various lithologies (4.0-7.0 ft., fill?).	Borehole drilled 0.0-9.0 ft. using 4" solid-stem augers. Site checked for radioactive contamination and hole gamma-logged by Eberline-TMA, Corporation.
							32.5				Bottom of borehole at 9.0 ft. Auger spoils were immediately replaced in the hole, 10-6-86.	8.5 ft. ground water observed.
												Description and classification of soil samples by visual examination.
SS = SPLIT SPOON; ST = SHELBY TUBE; D = DENNISON; P = PITCHER; O = OTHER											SITE	HOLE NO.
11 Branca Court (LODI)												610R

GEOLOGIC DRILL LOG				PROJECT		JOB NO.	SHEET NO.	HOLE NO.				
				FUSRAP		14501-138	1 OF 1	611R				
SITE			COORDINATES			ANGLE FROM HORIZ		BEARING				
11 Branca Ct. (LODI)			N 2092; E 3563			Vertical		-----				
BEGUN	COMPLETED	DRILLER		DRILL MAKE AND MODEL		SIZE	OVERBURDEN	ROCK (FT.)	TOTAL DEPTH			
10-6-86	10-6-86	MORETRENCH		B&S little beaver		4"	8.0		8.0			
CORE RECOVERY (FT./%)		CORE BOXES	SAMPLES	EL. TOP CASING	GROUND EL.	DEPTH/EL. GROUND WATER		DEPTH/EL. TOP OF ROCK				
/					42.5	7.0/35.5 10-6-86		/				
SAMPLE HAMMER WEIGHT/FALL		CASING LEFT IN HOLE: DIA./LENGTH			LOGGED BY:							
N/A		NONE			D. MCGRANE							
SAMP. TYPE AND DIAM.	SAMP. ADV. LEN CORE	SAMP. REC. CORE REC.	SAMPLE BLOWS "IN" % CORE RECOVERY	WATER PRESSURE TESTS			ELEV.	DEPTH	GRAPHICS	SAMPLE	DESCRIPTION AND CLASSIFICATION	NOTES ON: WATER LEVELS, WATER RETURN, CHARACTER OF DRILLING, ETC.
				LOSS IN G.P.M.	PRESS. P.S.I.	TIME IN MIN.						
							42.5					
							34.5				0.0 - 8.0 FT. SILTY SAND, (SM) . Fill and natural material; color stratified; fine to medium-grained; soft; poorly consolidated (loose); moist to saturated at 7.0 ft. 0.0-0.5 ft., moderate brown (5 YR 3/4), numerous grass roots and organics. 0.5-3.0 ft., dark reddish brown (10 R 3/4); few rounded pebbles of mixed lithologies; piece of plastic (3.0 ft.); fill? 3.0-4.0 ft., moderate brown and mottled grayish black (N2). 4.0-8.0 ft., dark reddish brown.	Borehole drilled 0 - 8.0 ft. using 4" solid-stem augers.
											Bottom of boring at 8.0 ft. Borehole backfilled with spoils, 10-6-86.	Site checked for radioactive contamination and hole gamma-logged by Eberline-TMA, Corp. Auger refusal at 8.0 ft. Cobble? Groundwater observed, 10-6-86.
												Description and classification of soil samples by visual examination.
SS = SPLIT SPOON; ST = SHELBY TUBE; D = DENNISON; P = PITCHER; O = OTHER											SITE	HOLE NO.
											11 Branca Ct. (LODI)	611R